

Check Beispiele

JMX Check

```
CHECKID=CU_JMX0
# Name des Checks
CU_JMX0.NAME=JMX Tomcat CU# Alarmierung OFF ; ONERROR ; ONWARN ; ONCHANGE ; ONWARNONC ;
ONERRORONC
CU_JMX0.ALERTING=OFF
# Mailmodul fuer Alarmierungen
CU_JMX0.MAILMODUL=MAIL_ALL
CU_JMX0.CHECKINTERVALL=5
CU_JMX0.GROUP=JMX
CU_JMX0.TYPE=JMX
CU_JMX0.PORT=8008
CU_JMX0.SERVER=LOCALHOST
CU_JMX0.USER=monitorRole
CU_JMX0.PASSWORD=password
CU_JMX0.VALUE=CPULOAD,RAMPERCENTCU_JMX0.ERRORCONDITION=#{CPULOAD}>99
CU_JMX0.WARNCONDITION=(#{CPULOAD}>89) || (equals("#{LASTRUN}", 'UNKNOWN'))
CU_JMX0.OKCONDITION=#{CPULOAD}<90CU_JMX0.DETAILS='#{STATUS}'+'<br><b>CPU : </b>' +
'#{CPULOAD}' + ' % <br><b>RAMUSED : </b>' + '#{RAMUSED}' + ' MB (' + '#{RAMPERCENT}' +
'%)<br><b>RAMCOMMITTED : </b>' + '#{RAMCOMMITTED}' + ' MB<br><b>RAMFREE : </b>' + '#{RAMFREE}'
+ ' MB<br><b>HDDFREE : </b>' + '#{HDDFREE}' + ' MB<br> Status vorherige Pruefung :
'+ '#{LASTRUN}'
```

Revision #1

Created 5 years ago by [Daniel Schulz](#)

Updated 5 years ago by [Daniel Schulz](#)